


Data Center Modul DCM 19" heavy duty server rack, width 600 and 800, stationary, with side panels



**DCM 19" heavy duty server rack,
width 600 and 800, stationary, with side panels**

Order number

Width [mm]	Height [mm]	Height [U]	Depth T [mm]	Chassis depth t [mm]
---------------	----------------	---------------	-----------------	-------------------------

800	2000	42	1200	740
-----	------	----	------	-----

**DB8GCGSSCFB
XXX8**

- Perforated front door
- Perforated double wing door at the back
- Special 19" server extrusions for mounting all trade standard 19" servers
- Built-in components in acc. IEC 297-3
- Cable entry via bottom and top cover
- Cable entry on the top cover, can be completely removed at the rear, allowing top cover removal and replacement after cabling

Jumpering compartment

- At the front: 80 mm

Load rating

- 15,000 N static

Degree of protection

- IP 20

Tests

- Earthing in acc. with DIN EN60950
- IP test in acc. with DIN 40 050 / IEC 529

Flow cross-section

- Perforation 83%

Data Center Modul DCM 19" heavy duty server rack, width 600 and 800, stationary, with side panels

Material / Finish

- Basic rack: extruded aluminium, polished
- Corner piece: die-cast aluminium, polished
- Doors: sheet steel, powder-coated texture
- Covers: sheet steel, zinc-passivated, powder-coated texture

Colour

- Visible surfaces of the covers, RAL7021 dark grey

Supply schedule

1 basic rack
4 19" server extrusions, sheet steel incl. HU numbering
1 top cover with cable entry (three-piece sliding plates, can also be opened completely)
2 side panels with quick connectors
1 front door, single, perforated, with handle and mounting for cylinder lock
1 rear double wing door, perforated, sheet steel, with handle and mounting for cylinder lock
4 levelling feet
1 complete earthing set (VDE 0100)

How supplied

- assembled

Please note

Also order mounting adapter for 19" server extrusion for mounting Knürr accessories.